

VX1937wm

Enhance productivity and Entertainment

48cm/19" WideScreen LCD Monitor VX Series



- > **Fast ClearMotiv® 5ms video response**
Video response as fast as 5ms enables digital HD broadcast-quality video.
- > **100,000:1 Dynamic Contrast Ratio**
Provides for darker black levels and better overall front-of-screen performance.
- > **OptiSync multiple analogue/digital inputs**
Multi-mode input technology supports both digital (DVI-D with HDCP) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OnView® controls for superior screen adjustability**
- > **Windows7 certified**
- > **ViewSonic Wizard included**
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > **PC and Mac compatible**
- > **ECO Mode**
Environmentally-friendly Eco-mode reduces power consumption and extends backlight life.
- > **SRS Premium Sound**
Extends the speaker frequency range, delivering better response and sound performance.

Model No.	VX1937wm	VX1937wma	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (Typ.) Dynamic Contrast Ratio Viewing Angle (CR ≥ 10 / CR ≥ 5) Response Time (ms) Pixel Pitch (H × V) Panel Surface Light Source (Hours) Color Support (Millions of colours)	48cm/19" wide Color TFT Active Matrix LCD with 16:10 aspect ratio 1440 × 900 native resolution 300 1,000:1 100,000:1 160° (H), 160° (V) 5ms (Typ) 0.2835 mm (H) × 0.2835mm (V) Anti-Glare, Hard coating (3H) 50,000 hrs (Typ.) 16.7 M (6-bits + Hi FRC)	
INPUT	Analog Sync Frequency (Fh / Fv)	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync / Composite Sync / SOG Fh = 24 ~ 83 kHz ; Fv = 50 ~ 76 Hz, (VGA)	
COMPATIBILITY	PC Mac	VGA up to 1440×900 non-interlaced Power Mac, up to 1440×900	
CONNECTOR	Analog Digital Audio Power	1×15 pin mini D-sub 1×DVI 1×3.5 mm Audio in Built-in power Adapter, 3-Pin plug	1×15 pin mini D-sub Built-in power Adapter, 3-Pin plug
SPEAKER	Speaker	2w x2 (SRS Premium Sound)	-
POWER	Voltage Consumption (W) Save mode (W)	AC 100-240V (Universal); 50/60Hz(Switch) 33 W (typ.) w/o Audio / 48 W (Max) with Audio ≤ 0.2w	
CONTROLS	Basic OnView / OSD	[1], [2], Power, Down[▼], Up[▲] Auto Image Adjust, Contrast/Brightness, Input Select, D-SUB, DVI, Audio Adjust, Volume, mute, Color Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B], Information, Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Response Time, Aspect Ratio, Display Mode, ECO Mode, Setup Menu, Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off, Memory recall	
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 20 - 90 (%)	
DIMENSIONS (WxHxD)	Physical (w/stand)	444.2×374.6×190 (mm), 17.49×14.72×7.48 (in)	
WEIGHT	Net (w/stand)	3.89 kg / 8.58 lb	
REGULATIONS		UL, CUL, FCC-B (ICES), CB, CE, CES-003B, ISO13406-2, TUV/GS, ERGO, TUV-S, NOM, GOST-R, HYGIENIC (20 copies), CCC, BSMI, PSB, C-TICK, KC, SASO, WEEE, RoHS, SASO, Ukraine	
WALL MOUNT (mm)	VESA® Mount Compliant	100mm × 100mm	

For more product information, visit us at ap.viewsonic.com

ViewSonic® See the difference™ 