

PJD5111

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH BRILLIANTCOLOR™ TECHNOLOGY

Easy to use, easy to afford

The ViewSonic PJD5111 is a practical projector that offers outstanding value and the best SVGA performance available. This native SVGA resolution projector supports high definition signals and projects 2500 lumens for clear, bright images in most lighting conditions. At only 2.3kg, it is light and compact, making it ideal for the mobile presenter or to move from room to room in the office or on a campus. Texas Instruments' BrilliantColor™ technology delivers brilliant, true-color and high contrast images for viewing presentations, charts, or video. With extensive connectivity, including two RGB inputs and one RGB output, the PJD5111 is an excellent multifunctional data/video projector. The Eco-mode function reduces the fan noise output for less distraction during important presentations and even extends the lamp life up to 4000 hours*. The PJD5111 is perfect for users looking for an easy to use, versatile and portable projector at a great price.



Versatile presentations anywhere

> Bright in virtually any setting

Packs 2,500 ANSI lumens in just 2.3kg, and with a high 2800:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

> BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

> Eco-mode extends lamp life

Extend the life of your lamp up to 4000 hours** and reduce noise output.

> Off to Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic
See the difference™ 

PJD5111

LIGHT, BRIGHT AND PORTABLE PROJECTOR

ViewSonic®
See the difference™ 



Optional Accessories

- >Replacement lamp RLC-047
- >Wireless G presentation gateway WPG-150

Projection Distance 4:3 Screen		Screen Size 4:3 Screen	
M	feet	m	Inches
1.2	3.9	0.7~0.8	28.0~31.7
1.5	4.9	0.9~1.0	35.2~40.0
1.8	5.9	1.1~1.2	42.3~48.0
2	6.6	1.2~1.3	47.4~53.7
3	9.8	1.8~2.2	70.3~79.7
5	16.4	3.3~3.4	117.6~133.3
11.3	37.1	6.4~7.6	250~300

Model No.VS12440

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	SVGA 800×600 (Native) / SXGA 1280×1024 (compressed)
	Lens	1.1× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/-40 degrees
	Size	30" -300"
	Throw Distance	0.9m-10.9m
	Throw Ratio	1.86:1-2.04:1
	Lamp	189 watt
	Lamp Life (Normal / Eco Mode)	3000 / 4000 hours
	Brightness	2500 Lumens
Contrast Ratio	2800:1 (with DCR)	
Aspect Ratio	4:3 (native) & 16:9	
Color Gamut	85 % NTSC 1931 CIE	
AUDIO	Speaker	1×5W
	Amplifier	1W at THD<10%
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 30-70 KHz, Fv: 50-87 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 1280×1024 (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	Component	2 × 15-in mini -D-Sub (sharer with RGB)
	RGB Output	1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1×RS-232 (8 Pin Mini-Din)
	POWER	Voltage
Consumption		242W (Typical) / <5W (Stand-by mode)
CONTROLS	Basic	POWER, Keystone/up and down keys, Left/BLANK, MENU/EXIT, Right/ Panel key lock, AUTO, MODE/ENTER, SOURCE
	OSD	Display: Screen color, aspect ratio, keystone, position, phase, H. size, digital zoom Picture: Preset mode: brightest, standard(Video),daylight, ViewMatch(PC), cinema, user 1/user 2, brightness, contrast, color, tint, sharpness, brilliant color, color temp., save settings) Source: Quick auto search System setting (Basic): Language, projector position, auto power off, blank timer, panel key lock, timer controller, splash screen System setting (Advanced): Qquick cooling, high altitude mode, DCR, active VGA out, audio settings, menu settings, closed caption, lamp settings, security setting, reset all settings Information: Current system status (source, preset mode, resolution, color system, equivalent lamp hour)
OPERATING CONDITION	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10% - 90% (non-condensing)
	Altitude	0~1,800m (6000ft), operational up to 3,048m (10000ft)
NOISE LEVEL	Normal / Eco Mode	30dB / 26dB
DIMENSIONS (W x D x H)	Physical	264 × 225 × 96.4 (mm) / 10.4 × 8.86 × 3.8 (in)
	Packaging	340 × 273 × 190 (mm) / 13.39 × 10.75 × 7.48 (in)
WEIGHT	Net	2.3 kg (5.08lb)
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Rev.1.0

Headquarters:
381 Brea Canyon Road,
Walnut, CA 97189, U.S.A.
salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific:
9F, No. 1 92 Lien Chien Road,
Chung Ho, Taipei, R.O.C.
www.viewsonic.com.tw

ViewSonic Singapore:
1 Kaki Bukit Road 1,
#03-40 Enterprise One,
Singapore 415934

ViewSonic Australia:
Unit 4, 44 Dickson Ave, Artarmon
NSW 2064, Australia
www.viewsonic.com.au

ViewSonic Korea:
#622, 6F, Gangbyeon Hanshin Core Bldg.,
350, Mapo-dong
Mapo-gu, Seoul 121-703, Korea

ViewSonic India:
Unit No 2, 3 & 4, Ground Floor,
Tribhuvan Complex, Ishwar Nagar,
Mathura Road,
New Delhi - 110065

For more product information, visit us on the web at ViewSonic.com